

EN



**Environmental Assessment  
for a Premarket Notification for Polyvinylimidazole**

1 **Date:** 7 October 2002

2 **Name of sponsor:** (1) Gordon Burns and (2) Robert Ellsworth

3 **Address** (1) 899 Adams Street, Suite A, St Helena, CA 94574  
(2) 1770 Dean York Lane, St Helena, CA 94574

4. **Description of the proposed action**


- a) **Requested action** Seeking FDA approval for use of the subject food-contact substance, polyvinylimidazole ("PVI"), in filter media to be used for the reduction of metals and sulfides in alcoholic beverages.
- b) **Need for action** Elevated metal content in alcoholic beverages presents a difficult problem in their reduction to acceptable levels. Filter media containing PVI accomplishes this. Sulfide off characters in alcoholic beverages can also be reduced to acceptable levels with the use of specially prepared PVI filter media
- c) **Locations of use:** PVI will be incorporated into filter media that will be used at alcoholic beverage production facilities at various locations around the country.
- d) **Locations of disposal:** We expect that used filter media, containing minute quantities of PVI, will be disposed of along with municipal solid waste, i.e., deposited in municipal solid waste landfills or combusted along with municipal solid waste

5. **Identification of substances that are the subject of the proposed action**


Described below are the polymer and its four ingredients.

**Polyvinylimidazole**

Empirical formula.



Structural formula



000028

|                 |   |       |
|-----------------|---|-------|
| Molecular mass: | Cannot be determined due to the insolubility in all solvents. |       |
| Appearance:     | white to off-white powder                                     |       |
| Specifications: | Loss on drying (1h, 140°C, vacuum)                            | ≤ 5   |
|                 | %   | 26.0  |
|                 |   | ≤     |
|                 |   | ≤     |
|                 |   | ≤     |
|                 |   | ≤     |
|                 |   | ≤     |
|                 |   | ≤     |
|                 |   | ≤ 0.5 |
|                 |   | ≤ 1.0 |
|                 | 1-Vinylpyrrolidone (GC)                                       | ≤     |
|                 | 10.0 mg/kg  |       |
|                 | 1-Vinylimidazole (HPLC)                                       | ≤     |
|                 | 10.0 mg/kg  |       |
|                 | 1,3-Divinylimidazolidinone (GC)                               | ≤     |
|                 | 2.0 mg/kg   |       |
|                 |   | ≤     |

**Chemical name:**


- Crosslinked terpolymer of 1-vinylimidazole, 1-vinylpyrrolidone and 1,3-divinylimidazolidinone

**List of ingredients / specifications:**

1-Vinylpyrrolidone  
 1-Vinylimidazole  
 1,3-Divinylimidazolidinone

**1-Vinylpyrrolidone**

Formula

C<sub>6</sub>H<sub>9</sub>NO

Molecular weight:

111.14

Description:

Colorless liquid

Specification

Assay

&gt; 99.5 %

Impurities

(= Pyrrolidone and others)

&lt; 0.5 %

Water

&lt; 0.1 %


Melting point

13.5-14.0 °C

Polymer content

&lt; 0.05 %


000030

**1-Vinylimidazole**Formula:  $C_5H_6N_2$ 

|                   |                               |          |
|-------------------|-------------------------------|----------|
| Molecular weight: | 94.12                         |          |
| Description:      | Colorless to yellowish liquid |          |
| Specification:    | Assay                         | > 99.5 % |
|                   | Impurities:                   |          |
|                   | Imidazole                     | < 0.3 %  |
|                   | Pyrrolidone                   | < 0.2 %  |

**1,3-Divinylimidazolidinone**

Formula



|                  |                           |          |
|------------------|---------------------------|----------|
| Molecular weight | 138.2                     |          |
| Appearance       | white to yellowish powder |          |
| Specification    | Assay                     | ≥ 99 %   |
|                  | Melting point             | 66-68 °C |

000031

Formula

Molecular weight

Appearance

Specification

6 **Introduction of substances into the environment**

- a) **Introduction of substances into the environment as a result of manufacture:** No extraordinary circumstances apply to the manufacture of the food-contact substance
- b) **Introduction of substances into the environment as a result of use.** Little or no introduction of PVI into the environment will result from its use because this food-contact substance is almost completely incorporated into food-contact filter media and essentially all of it is expected to remain with this media throughout its use.
- c) **Introduction of substances into the environment as a result of disposals.** The filter media containing the PVI is expected to be disposed of in municipal solid waste landfills and/or incinerators after use. With regard to landfilling, we expect insignificant levels of the substances to migrate from the filter media in landfills because (1) migration studies previously submitted to FDA (our original petition dated April 9, 1999 and Exhibit E of FCN 000141) show insignificant migration potential; (2) the concentration of the PVI substance in the filter media is minimal; and (3) PVI is highly insoluble. In addition, the introduction of these substances into the environment will not threaten a violation of the Environment Protection Agency's regulations in 40 CFR Part 258 that pertain to landfills. With regard to combustion, PVI is composed of carbon, hydrogen and nitrogen, elements commonly found in municipal solid waste.<sup>1</sup> The complete combustion of this substance will produce carbon dioxide, water and oxides of nitrogen. Because the market volume<sup>2</sup> of the food-contact substance is a very small fraction of the municipal solid waste generated and disposed in the United States, adding this substance to waste that is combusted will not significantly alter the emissions from municipal waste combustors. Because of the low levels of the combustion products compared to the amounts currently generated by municipal waste combustors, we do not expect that the combustion of this substance will cause municipal waste combustors to threaten a violation of applicable federal and state emissions laws and regulations

<sup>1</sup> *Municipal Waste Combustors - Background Information for Proposed Guidelines for Existing Facilities*, EPA-450/3-89-27e, United States Environment Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, NC 27711; August 1989, Table 2.2-1.

<sup>2</sup> Wine production in the USA is approximately 500,000,000 gallons per year. See Attached Key Facts Chart. Since wine production has remained static for the past several years, we make the assumption that this estimate is based on total fifth year production. It is estimated that approximately one percent of this volume may be treated for sulfide removal using the filter media. Based on calculations in paragraph 9, scenario #3, approximately 2.3 kilograms of PVI would treat 50,000 gallons, and thus annual PVI usage would be approximately 230 kilograms. This weight is inconsequential when compared with the weight of solid waste generated and disposed of in the United States.

000032

7. **Fate of substances released onto the environment.** No information need be provided on the fate of substances released into the environment as the result of use and/or disposal the filter media with PVI, because, as discussed above, only minute quantities, if any, of substances will be introduced into the environment as a result of use and/or disposal of the filter media. Therefore, the use and disposal of the food-contact substance is not expected to threaten a violation of applicable laws and regulations, *e.g.*, the Environmental Protection Agency's regulations in 40 CFR Parts 60 and 258.
8. **Environmental effects of released substances:** No information need be provided on the environmental effects of substances released into the environment as a result of use and/or disposal of the filter media, because, as discussed under Item 6 above, only minute quantities, if any, of substances will be introduced into the environment as a result of use and/or disposal of the filter media. Therefore, the use and disposal of the filter media is not expected to threaten a violation of applicable laws and regulations, *e.g.*, the Environmental Protection Agency's regulations in 40 CRF Parts 60 and 258.
9. **Use of Resources:** The filter media containing PVI is intended to replace current wine treatment activities (some of which use ferrocyanide) that are less protective of the environment. Thus, there is no anticipated effect on the use of natural resources and energy associated with proposed substitute.

Current wine treatment activities, based upon 50,000 gallon batches, are as shown below.

#### CURRENT FILTER MEDIA PRODUCTION METHODS

An aqueous slurry, composed of 40 to 60% diatomaceous earth (DE), 1 to 2 % resin binder, and the balance of cellulose fibers, is distributed across a moving vacuum belt, which dewater the slurry forming a continuous sheet, often 48 to 50 inches wide, of moist material. The machine is usually a modified paper making machine. This continuous sheet is then dried in a forced air counterflow oven. After drying, this continuous sheet is fiberized into a coarse granular like material.

The grade or tightness of the filter media is dependent upon the type and proportions of DE and type and proportions of cellulose fibers.

The Gusmer-Cellulo Company of Fresno, California uses about 640 tons of DE per year, and about 560 tons of cellulose per year. They estimate that they have between 20 to 30% of the filter pad and filter media market in the USA.

#### ROUTINE WINE FILTRATION METHODS FOR CLARIFICATION AND MICROBIAL STABILITY

Scenario #1, a typical winery filtration of 50,000 gallons of wine from the fermenter to the bottle, using filter media.

1st filtration (coarse or clarifying) The expected flow rates are between 5 and 6 gallons per hour per square meter of filtering surface and the expected run time would be 5 hours to exhaustion. This calculates to an average of 30 gallons per square meter of filtering surface and a requirement of 60 kilograms of filter media.

2nd filtration (bright) The expected flow rates are between 3 and 5 gallons per hour per square meter of filtering surface and an expected run time of 6 hours to exhaustion. This produces an average of 25 gallons per square meter of filtering surface and a requirement of 70 kilograms of filter media.

000033

3rd filtration (polish). The expected flow rates are between 2 and 3 gallons per hour per square meter of filtering surface and an expected run time of 8 hours to exhaustion. This produces an average of 18 gallons per square foot of filtering surface and a requirement of 98 kilograms of filter media

For the life of this 50,000 gallon batch of wine, the filtrations will have consumed 228 kilograms of filter media. Each batch of wine would consume 114 kilograms of DE and 114 kilograms of cellulose fibers

In the production of 50,000 gallons of wine (approximately 400,000 pounds), the consumed filtering material amounts to about 0.12% by weight of the wine

While the above example is based on 50,000 gallons of wine, smaller or larger quantities would be roughly proportional in filtration requirements

#### COMPARISON OF CURRENTLY APPROVED METHODS FOR REMOVAL OF SULFIDES AND METALS WITH THE PROPOSED PVI FILTER MEDIA METHOD

*Scenario #2* The currently approved method for the removal of sulfides and metal from alcoholic beverages

For the reduction of sulfides in alcoholic beverages, copper sulfate is added up to levels of 3 9 ppm, then the beverage is treated with a ferrocyanide compound, Cufex, in amounts of 1 to 10 pounds per 1000 gallons. The wine must then carefully filtered to remove any traces of ferrocyanide

The first filtration to remove Cufex would be done with the same grade of filter media as the 2nd filtration in Scenario #1 above. Both the flow rate and the run time would be reduced considerably due to the high loading caused by the Cufex. We would expect to filter approximately 9 gallons per square meter of filtering surface.

For the 50,000 gallon batch of wine, with an addition of 2.3 kilograms per 1000 gallons of Cufex, 208 kilograms of filter media would be required for this filtration

115 kilograms of a ferrocyanide compound would be discarded along with about 104 kilograms of DE and 104 kilograms of cellulose fibers.

*Scenario #3.* Proposed use of PVI filter media for the reduction of sulfides in wine.

The threshold of organoleptic detection is in the range of 1 0 to 1 5 ppb. A wine with 3 0 ppb of sulfide can be reduced to less than 1.0 ppb with PVI filter media at a ratio of 5200 gallons per kilogram of filter media. 9.5 kilograms of filter media would be required to process the 50,000 gallon batch of wine and would use approximately 3 8 kilograms of the PVI polymer and 5 7 kilograms of cellulose fibers.

10. **Mitigation measures:** Based on a review of adequate data and information, no adverse environmental effects have been identified, so mitigation measures are inappropriate.
11. **Alternatives to the proposed action:** Based on a review of adequate data and information, no adverse environmental effects have been identified. Furthermore, as discussed in Item 9 above, the proposed use of PVI will minimize environmental impacts when compared to the current metal and sulfide reduction methods which employ a ferrocyanide compound.

000034

12. **List of preparers** Robert Ellsworth, Consulting Chemist, St. Helena, CA  
Gordon Burns, Technical Director, E T S Laboratories, St. Helena, CA

13. **Certificate:** "The undersigned official certifies that the information presented is true, accurate, and complete to the best of the knowledge of the preparers"

14. 7 Oct 02

[Redacted signature box]

(Signature of preparer)

Gordon Burns, Technical Director

(Name and title of preparer, printed)

[Redacted signature box]

(Signature of preparer)

Robert M. Ellsworth, Consulting Chemist

(Name and title of preparer, printed)

15. **Attachments:** Key Facts Chart



**WINE INSTITUTE**  
THE VOICE FOR CALIFORNIA WINE  
**KEY FACTS**

125 MARKET STREET, SUITE 200  
SAN FRANCISCO, CA 94102  
PHONE: 415.561.0101  
FAX: 415.561.0102

**WINE PRODUCTION\***

California produces 90% of total U.S. wine production  
(in thousands of gallons)

(Updated September 2000)

| Year | California | U.S.    |
|------|------------|---------|
| 1998 | 443,693    | 494,097 |
| 1997 | 483,555    | 533,329 |
| 1996 | 418,376    | 460,081 |
| 1995 | 397,042    | 437,034 |
| 1994 | 357,819    | 396,109 |
| 1993 | 416,076    | 451,883 |
| 1992 | 377,000    | 412,595 |
| 1991 | 369,305    | 400,098 |
| 1990 | 379,726    | 417,157 |
| 1989 | 367,914    | 409,715 |
| 1988 | 433,569    | 477,380 |
| 1987 | 390,737    | 439,852 |
| 1986 | 439,315    | 484,575 |

\* Removals of still wine from fermenters. Excludes substandard wine produced as distilling material. Also excludes increases after amelioration, sweetening, and addition of wine spirits  
History revised.

Source: Wine Institute/US WineStats from BATF data

Qualified journalists and Wine Institute members requiring further information may contact  
Communications Department

Suggestions to [webmaster@wineinstitute.org](mailto:webmaster@wineinstitute.org)  
Copyright © 1997-2001 Wine Institute. All rights reserved

000036